

Fosroc® Nitobond AR and Nitobond HAR



constructive solutions

1
CI/SfB:
December 2009

Polymer emulsion bonding agents

Uses

Nitobond AR and Nitobond HAR are recommended primers for the Renderoc cementitious repair systems.

Nitobond AR is also recommended as a curing membrane for Renderoc repairs. It may also be used as an economical dust proofer for non-trafficked cementitious surfaces.

Advantages

- Single component No site mixing
- Easy to use Ready to use straight from the container
- High bond strength Excellent bond strength between Renderoc systems and concrete
- Cost effective Economical in use
- Curing aid Can be used as curing membrane for Renderoc systems

Description

Nitobond AR and Nitobond HAR are single component polymer emulsion systems designed as bonding agents and curing membranes for Renderoc repair products. They may also be used as concrete surface sealers in non-traffic areas.

Application instructions

Preparation

All surfaces should be clean and free from dust and contamination.

Application

Nitobond AR and Nitobond HAR are supplied ready for use when used as bonding primers or curing membranes. When used as a surface sealer Nitobond AR should be diluted 1:1 with water for the first coat and as supplied for the second coat. Application should be by spray, brush or medium pile roller. Care should be taken to ensure complete and thorough wetting of the surface.

Cleaning

Wash all equipment with clean water immediately after use.

Estimating

Supply

Nitobond AR	1 litre and 5 litre bottles, 25 litre drums
Nitobond HAR	5 litre bottles, 25 litre drums

Coverage and yield

As Primer

Nitobond AR & Nitobond HAR	4-6m ² /litre
----------------------------	--------------------------

As Curing Membrane

Nitobond AR	6-8m ² /litre
-------------	--------------------------

As Surface Sealer

Nitobond AR	6-10m ² /litre
-------------	---------------------------

Limitations

Do not use Nitobond AR or Nitobond HAR when the temperature is below 5°C and falling.

Storage

Store in dry conditions at 5°-25°C. Shelf life is 12 months if stored in dry conditions. Protect from frost.

Precautions

Health and safety

For further information refer to appropriate Product Safety Data Sheet.

Fire

Nitobond AR and Nitobond HAR are non-flammable.

Fosroc and Nitobond are trademarks
Fosroc International Limited



Important note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Services, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification of information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation of information given by it.

Fosroc Limited

Drayton Manor Business Park
Coleshill Road, Tamworth,
Staffordshire B78 3TL. UK

www.fosroc.com

telephone:
+44 (0) 1827 262222

fax:
+44 (0) 1827 262444

email:
enquiryuk@fosroc.com



Certificate number FM 610