



Sovereign Flexi Tape

Sovereign Flexi Tape is a synthetic butyl/rubber based reinforced sealant strip.



Product Code
30610195

Description

Flexi-Tape is a fleece covered membrane roll used in conjunction with Liquid DPM & Gas Barrier. It is specifically designed for use as reinforcement at high stress points such as the floor/wall juncture and at joints.

The Flexi-Tape is bedded in to the wet first coat once tacky and is over-coated with a second coat of Liquid DPM & Gas Barrier, thus ensuring continuity and integrity of the system.

Colour:	Grey
Roll Size:	2 mm x 100 mm x 5 m
Tolerance:	Thickness + 0.2 mm, width 2 mm
Service Temperature Range:	-40°C to +90C

Preparation

All surfaces must be thoroughly clean, dry and free from frost, grease and loose materials.

Application

The Flexi-Tape is bedded in to the wet first coat, and once tacky, is over-coated with a second wet coat.

Packaging

Supplied as a single roll 5 m length.





HEALTH AND SAFETY

This product is classified as non hazardous.

Storage: Above ground in dry conditions.

Shelf Life: 12 months unopened.



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign

the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

