

Description

rbs Formseal is a polyurethane coating specifically formulated to give formwork an impervious and protective finish. rbs Formseal is designed for sealing and protecting general formwork enabling multiple re-use. It will leave a tough, flexible coating improving the life expectancy of the formwork. Quick drying and applied by brush or roller.

Advantages

- Single coat application.
- Easy to apply by brush or roller.
- Improves formwork release.
- Life of formwork greatly increased.
- Provides a uniform surface and eliminates moisture absorption.
- Stripping and cleaning time of formwork greatly reduced.

Directions For Use

- All surfaces must be clean and untreated.
- Fill all holes and imperfections with a suitable formwork repair material.
- Apply an even coat of rbs Formseal with a brush or roller to the face and edge preferably with the form horizontal.
- Apply a second coat 1-4 hours later or as soon as the first coat is dry.
- If applying a second coat more than 12 hours later, lightly sand the first coat prior to the second application.
- Stack formwork separately in a well ventilated area.
- Allow to cure for at least 48 hours before use.
- Clean all equipment with rbs Sitewash.

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

Technical Data

Appearance	Low viscosity clear liquid
Specific Gravity @ 15.6°C	0.97
Flash Point (PMCC)	47°C min
Viscosity	Brushing consistency
Coverage	7-9m ² per litre
Recommended Dilution	None required

Packaging

rbs Formseal is available in a 5 litre container.

Storage

Unopened containers of rbs Formseal should be stored under dry, frost-free conditions away from direct sunlight. The shelf life is 12 months when stored in original, unopened packaging.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy themselves that each product is fit for the purpose for which they intend to use it. Ensure that the actual conditions of use are suitable, and that in the light of our continual research and development programme, the information relating to each product has not been superseded.

Resapol 
Foundation

Giving back with every pack

For more information on the Resapol Foundation, please visit our website at www.resapol.com.

Resapol Ltd

Unit D4, Moss Industrial Estate, Walter Leigh Way,
Leigh, Lancashire WN7 3PT

T 0800 083 1942 E sales@resapol.com

www.resapol.com