

Description

Environmentally friendly water based concrete curing membrane. A blue grade version is also available to help in identification during application.

Advantages

- Economical and easy to use.
- Tinted grade available to assist identification during application.
- Prevents premature drying out of the concrete surface reducing the risks of surface cracking and reducing the risk of surface dusting.
- Improves the durability of the concrete surface.
- Silane compatible, guaranteed not to adversely affect the bond of subsequent coatings, screeds or renders.
- One coat spray application.

Directions For Use

For freshly cast surfaces – Apply as soon as final tamping or trowelling has been finished. If surface water is present a second application is desirable as soon as the surface water has evaporated. Make sure the correct rate is used to avoid ponding as it may glaze the surface of the concrete.

For surfaces struck from shuttering – Flood coat with water as soon as the formwork is struck, apply the chosen grade as soon as the water has run off. If this is not carried out it is possible that the curing compound will be “sucked” below the concrete surface leaving the surface unprotected. If the Tinted grade has been used UV light may not be able to act upon the “fugitive dye” thus leaving the concrete with a permanent colour. This advice is applicable whatever grade you may be using.

Note: Care should be taken that over spray does not get onto paint or glass as it may cause permanent damage if not rinsed off immediately.

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

Technical Data

Colour	Clear or tinted blue
Coverage	5-6 sq.mts per litre should be sufficient

Packaging

rbs Greencure WB is available in 5, 20 & 200 litre containers. IBC's are available on request.

Storage

Store in dry, frost free conditions. Away from heat and direct sunlight. Keep containers tightly closed. rbs Greencure WB has a shelf life of 1 year in sealed container when stored as recommended.

Health & Safety

When working with rbs Greencure WB suitable protective clothing, eye/face protection and gloves should be worn.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy themselves that each product is fit for the purpose for which they intend to use it. Ensure that the actual conditions of use are suitable, and that in the light of our continual research and development programme, the information relating to each product has not been superseded.

Resapol 
Foundation

Giving back *with every pack*

For more information on the Resapol Foundation, please visit our website at www.resapol.com.

Resapol Ltd

Unit D4, Moss Industrial Estate, Walter Leigh Way,
Leigh, Lancashire WN7 3PT

T 0800 083 1942 E sales@resapol.com

www.resapol.com