

Description

rbs Greenwallseal is a high performance clear, solvent free water repellent specially formulated to prevent water penetration to brick, stone, concrete, pebbledash, rendering and other mineral substrates. rbs Greenwallseal penetrates deeply into the surface treated to provide effective long term water repellency. Once cured Greenwallseal will leave a breathable coating enabling water vapour to move through the substrate to the air whilst still repelling liquid water.

Advantages

- May effect the substrate appearance for a short period.
- An effective water repellent for use on concrete, brick, stone, render and pebble-dashing.
- Provides improved durability and beading effect.
- A solvent free, environmentally friendly product.
- Non-flammable.
- Easily applied by low pressure spray equipment.
- May be applied to damp surfaces.
- Breathable.
- Penetrates deep into substrate to provide long term water repellency.

Limitations

- rbs Greenwallseal should not be applied below 10°C.
- Do not apply when raining or when rain is imminent.
- rbs Greenwallseal should not be used on painted surfaces, wood, plastic or rubber.
- Allowing the first coat to dry may prevent penetration of the second coat, always apply the second coat within 1 hour, or before the first coat is dry.
- Do not use in fishponds.
- Do not use detergents to clean the substrate prior to use of rbs Greenwallseal as it will dramatically reduce the beading effect.

Directions For Use

- All surfaces to be treated must be clean, sound, free from dirt, mould, algae, grease or other contaminants—they may be damp but must be free of standing water.
- Any necessary repairs should be carried out before application of rbs Greenwallseal.
- It is supplied ready for use but must be shaken well before use.
- It can be applied by brush, spray or roller.
- When applying on vertical surfaces it should be

applied from the bottom up.

- Ensure the whole area to be treated is saturated, any puddling should be addressed 15-20 minutes after initial application.
- rbs Greenwallseal is applied as a two coat system, the second coat being applied whilst the first coat is still wet– within 1 hour of initial application.

Technical Data

Appearance	Milky white
Composition	Emulsified polysiloxane resin in water
Average Coverage	5-8m ² / litre

Packaging

rbs Greenwallseal is available in 5 and 20 Litre containers.

Storage

rbs Greenwallseal should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

Health & Safety

When working with rbs Greenwallseal suitable protective clothing, eye/face protection and gloves should be worn. For further health and safety information, please refer to the relevant Safety Data Sheet.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy themselves that each product is fit for the purpose for which they intend to use it. Ensure that the actual conditions of use are suitable, and that in the light of our continual research and development programme, the information relating to each product has not been superseded.

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

Resapol Ltd

Unit D4, Moss Industrial Estate, Walter Leigh Way,
Leigh, Lancashire WN7 3PT
T 0800 083 1942 E sales@resapol.com
www.resapol.com

Resapol Foundation

Giving back *with every pack*

For more information on the Resapol Foundation, please visit our website at www.resapol.com.