

Description

rbs Hardseal XS is a clear acrylic polymer resin sealer and is based on a carefully sourced blend of chemicals. It hardens, cures and effectively seals block paving, concrete driveways, paths & patios.

rbs Hardseal XS will greatly increase concrete surface anti-abrasion properties particularly on warehouse\ factory floors and is suited to power floated floors.

Advantages

- Protects many surfaces from abrasion and water penetration.
- Consolidates floor surfaces.
- Curing and sealing in one operation.
- Single component, ie no mixing involved.
- Can be used both internally and externally.

Directions For Use

- rbs Hardseal XS is supplied as a ready to apply product by brush, roller or non-atomising spray. Do not over apply and brush out any runs that may occur.
- After about 20 minutes the sealer should have soaked into the concrete, and then further coats should be applied until no more material is absorbed.
- Allow 2 to 3 hours to elapse between coatings. Normally 2 coatings are sufficient but on 3 coatings may be needed on very porous surfaces.
- Use only in well ventilated areas and away from sources of ignition.

Storage

rbs Hardseal XS should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months, if unopened.

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

Packaging

rbs Hardseal XS is available in 5 & 25 Litre Containers.

Technical Data

Appearance	Low viscosity clear amber liquid
Specific Gravity @ 15.6°C	0.911
Flash Point (PMCC)	43°C
Viscosity cSt @ 40°C	N/A
Coverage	5-6m ² per litre
Recommended Dilution	None required

Health & Safety

When working with rbs Hardseal XS suitable protective clothing, eye/face protection and gloves should be worn. Areas where this product is being applied must be well ventilated.

For further health and safety information, please refer to the relevant Safety Data Sheet.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded

Resapol 
Foundation

Giving back with every pack

For more information on the Resapol Foundation, please visit our website at www.resapol.com.

Resapol Ltd

Unit D4, Moss Industrial Estate, Walter Leigh Way,
Leigh, Lancashire WN7 3PT

T 0800 083 1942 E sales@resapol.com

www.resapol.com