

Description

rbs Tackcoat is a cold applied rapid-acting 40% cationic bitumen emulsion. When cured rbs Tackcoat forms a thin uniform film of bitumen on the road surface which gives an adhesive bond between a bituminous overlay and an existing surface. For best results, tack coating is strongly recommended when performing such tasks as overlaying with hot rolled asphalt, macadam or when patching or carrying out inlaid work.

rbs Tackcoat adheres exceptionally well, even in damp conditions. The overlay is held securely in place and the entry of water between road pavement courses is hindered.

Where to Use

- Carriageways
- Footways
- Car parks

Directions For Use

Preparation - Surface to be treated must be free from detritus, standing water, loose materials and oil spillage.

Application - rbs Tackcoat should be sprayed or hand applied between 0.3-0.6 l/m² (depending on the texture, porosity etc. of the surface) to give the thinnest film consistent with complete coverage.

Vehicular traffic should be kept off the treated area until the emulsion has fully broken, colour changes from brown to black. When emulsion has fully broken then apply the overlay.

Coverage

1 x 25kg container should cover approximately 40m²
1 x 200kg drum should cover approximately 320m²

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

Packaging

rbs Tackcoat is available in 25kg and 200kg containers.

Storage

Protect from frost. Bulk material should be circulated before use. Drums should be rolled frequently to avoid separation. For further information please refer to BS434-2 2006 Clause 5.2 Storage.

Standards

rbs Tackcoat is a CE Marked cationic emulsion to BS EN13808:2013 C40B. rbs Tackcoat also complies with the withdrawn BS434-1 Standard as a K1-40 Type emulsion.

Health & Safety

rbs Tackcoat is classified as hazardous to the aquatic environment. For further information refer to the relevant Material Safety Data Sheet.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy themselves that each product is fit for the purpose for which they intend to use it. Ensure that the actual conditions of use are suitable, and that in the light of our continual research and development programme, the information relating to each product has not been superseded.

Resapol 
Foundation

Giving back *with every pack*

For more information on the Resapol Foundation, please visit our website at www.resapol.com.

Resapol Ltd

Unit D4, Moss Industrial Estate, Walter Leigh Way,
Leigh, Lancashire WN7 3PT

T 0800 083 1942 E sales@resapol.com

www.resapol.com