

Safety data sheet according to 1907/2006/EC, Article 31

Printing Date: 10.12.2020

Version Number: 4.0

Revision Date: 10.12.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier:**

Trade name: *Bituthene*® *Primer S2* 

UFI: 3CC0-X0NF-000F-4RRE

#### 1.2 Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet:

#### Manufacturer/supplier:

GCP Applied Technologies (UK) Limited 487-488 Ipswich Road, Slough, Berkshire SL1 4EP

Tel: +44 (0)1753 490 000 Fax: +44 (0)1753 490 001

\*\*\*\*\*

De Neef Construction Chemicals BVBA Industriepark 8, 2220 Heist-op-den-Berg, Belgium.

Tel: +32 15 24 93 60 Fax: +32 15 24 80 72

www.gcpat.com

Further information obtainable from: msds.gcp@gcpat.com

#### **1.4 Emergency telephone number:**

For Chemical Emergency: (Spill, Leak, Fire, Exposure or Accident) - Call CHEMTREC (Day/Night) on:

Within USA & Canada : 800-424-9300, Outside USA & Canada : +1 703-741-5970

National emergency telephone number: CHEMTREC UK +(44)-870-8200418

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture:

#### Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

## 2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

GB

Version Number: 4.0

## Trade name: Bituthene® Primer S2

(Contd. of page 1)

Revision Date: 10.12.2020

Hazard pictograms



Signal word Warning

Hazard-determining components of labelling: Xylene

#### Hazard statements

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / protective clothing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Hazard description: Flammable

2.3 Other hazards: Restricted to professional users.

**Results of PBT and vPvB assessment:** 

**PBT:** Not applicable. **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

## 3.2 Chemical characterization: Mixture:

#### **Description:**

Mixture of substances listed below with non-hazardous additions.

For further information, please refer to the product technical data sheet.

Dangerous components:

2 anger ous components.			
CAS: 1330-20-7	Xylene	Flam. Liq. 3, H226	50-<100%
EINECS: 215-535-7		Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
Index number: 601-022-00-9			
Reg.nr.: 01-2119488216-32-XXXX			

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF INHALED: Call a doctor if you feel unwell.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

(Contd. on page 3)

(Contd. of page 2)

Printing Date: 10.12.2020

Version Number: 4.0

Revision Date: 10.12.2020

## Trade name: Bituthene® Primer S2

#### After swallowing:

Rinse mouth.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed: Dizziness

## 4.3 Indication of any immediate medical attention and special treatment needed:

If skin irritation occurs: Get medical advice/attention.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media:

Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water jet.

## 5.2 Special hazards arising from the substance or mixture: CO, CO2.

## 5.3 Advice for firefighters:

**Protective equipment:** Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

## 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling:

Flammable mixtures with air can be formed in emptied containers. Do not puncture, cut, drill, heat or weld uncleaned drums.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original packaging.

Use only outdoors or in a well-ventilated area.

#### Information about fire - and explosion protection:

Protect against electrostatic charges.

(Contd. on page 4)

Version Number: 4.0

Trade name: Bituthene® Primer S2

Use explosion-proof apparatus / fittings and spark-proof tools.



Keep ignition sources away - Do not smoke.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ground and bond container and receiving equipment.

# 7.2 Conditions for safe storage, including any incompatibilities: STORAGE

#### Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

7.3 Specific end use(s): No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters:

Additional information about design of technical facilities: No further data; see item 7.

Ingredi	Ingredients with limit values that require monitoring at the workplace:		
1330-20	1330-20-7 Xylene		
L	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV		
Ingredients with biological limit values:			
	1330-20-7 Xylene		
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid		

Additional information: Based on the lists valid at the date of SDS creation.

## 8.2 Exposure controls:

#### PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

#### **Respiratory protection:**

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Filter A/P2.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

EN 143.

(Contd. on page 5)

GR

Revision Date: 10.12.2020

Version Number: 4.0

## Trade name: Bituthene® Primer S2

## Protection of hands:

Protective gloves.

EN 374.

## Material of gloves:

Nitrile rubber, NBR Natural rubber, NR Chloroprene rubber, CR

## Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

## Eye protection:



Safety glasses with side shield protection.

EN 166.

## **Body protection:**

Use personal protective equipment as required.

Take off contaminated clothing.

SECTION 9: Physical and chemical properties			
9.1 Information on basic physical and chemical properties:			
GENERAL INFORMATION Appearance: Form: Colour: Odour: Odour: Odour threshold:	Liquid. Pink. Characteristic. Not determined.		
pH-value (~):	Not determined.		
Change in conditions:- Melting point/freezing point: Initial boiling point and boiling range: Flash point:	Undetermined. : >140 °C >24 °C		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	500 °C		
Decomposition temperature: Auto-ignition temperature: Explosive properties:	Not determined. Not determined. In use, may form flammable/explosive vapour-air mixture.		
EXPLOSION LIMITS Lower: Upper:	0.9 Vol % 8 Vol %		
Vapour pressure at 20 °C: Density at 20 °C: Vapour density: Evaporation rate:	6.7 hPa 0.9 g/cm <sup>3</sup> Not determined. Not determined.		
Solubility in/Miscibility with:- Water:	Not miscible or difficult to mix.		
	(Contd. on page 6)		

(Contd. of page 4)

Revision Date: 10.12.2020

GB

Version Number: 4.0

## Trade name: Bituthene® Primer S2

		(Contd. of page 5)
Partition coefficient: n-octanol/water:	Not determined.	
VISCOSITY Dynamic at 20 °C: Kinematic:	100 mPas Not determined.	
SOLVENT CONTENT VOC (EC): Molecular weight	68.95 % Not applicable.	
9.2 Other information:	No further relevant information available.	

## **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity:**

Stable under normal conditions. No further relevant information available.

#### **10.2 Chemical stability:**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

#### **10.3 Possibility of hazardous reactions**

No dangerous reactions known.

No further relevant information available.

10.4 Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5 Incompatible materials:** No further relevant information available.

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects:

11.1 Information on toxicological effects:		
ACUTE TOXICITY		
 Harmful if inhaled.		
LD/LC50 values relevant for classification:		
1330-20-7 Xylene		
Oral LD50 3,523 mg/kg (rat)		
Primary irritant effect		
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/irritation Based on available data, the classification criteria are not met.		
Inhalation: Harmful if inhaled.		
<b>Respiratory or skin sensitisation</b> Based on available data, the classification criteria are not met. <b>Other information :</b> <b>Repeated dose toxicity</b>		
Germ cell mutagenicity Based on available data, the classification criteria are not met.		
Carcinogenicity Based on available data, the classification criteria are not met.		
Reproductive toxicity Based on available data, the classification criteria are not met.		
STOT-single exposure Based on available data, the classification criteria are not met.		

STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. of page 6)

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing Date: 10.12.2020

Version Number: 4.0

Revision Date: 10.12.2020

## Trade name: *Bituthene® Primer S2*

Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

## 12.1 Toxicity:

AQUATIC TOXICITY No further relevant information available.

**12.2 Persistence and degradability:** No further relevant information available.

**12.3 Bioaccumulative potential:** No further relevant information available.

**12.4 Mobility in soil:** No further relevant information available.

#### ADDITIONAL ECOLOGICAL INFORMATION

General notes: Not known to be hazardous to water.

## 12.5 Results of PBT and vPvB assessment:

**PBT:** Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects: No further relevant information available.

## **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods:**

#### **Recommendation:**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European	European waste catalogue:		
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS		
08 04 00	08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)		
08 04 09*	08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances		

## UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

14.1 UN-Number ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name ADR, IMDG, IATA

PAINT RELATED MATERIAL

(Contd. on page 8)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing Date: 10.12.2020

Version Number: 4.0

Revision Date: 10.12.2020

Trade name: Bituthene® Primer S2

		(Contd. of page 7)
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	III	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user: Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A	
14.7 Transport in bulk according to Annex I MARPOL73/78 and the IBC Code:	I of Not Regulated	
Transport/Additional information:		
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3	
Tunnel restriction code	D/E	
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic

equipment – Annex II

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

GB

Version Number: 4.0

Trade name: Bituthene® Primer S2

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### **Relevant phrases:**

H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled.

#### **Department issuing SDS:**

Product Stewardship Department GCP Applied Technologies (UK) Limited 487-488 Ipswich Road, Slough, Berkshire SL1 4EP

Tel: +44 (0)1753 490 000 Fax: +44 (0)1753 490 001

The first date of preparation: 10.12.2020

Number of revision times and the latest revision date: 4.0 / 10.12.2020

(Contd. of page 8)

Revision Date: 10.12.2020