

## Description

rbs Bluelease QD is an extremely versatile quick drying high specification chemical release agent specially blended to give optimum release resulting in high class concrete finishes from most types of formwork.

## Advantages

- Quick drying release agent suitable for most types of formwork.
- Extremely economical due to the large coverage rates achieved when applied by spray equipment.
- Recommended for difficult and intricate casting work.
- Is not affected by rain.
- The evaporative carrier used in rbs Bluelease QD ensures a safe walking surface on soffit formwork with no contamination of the reinforcement.
- Prior to the application of subsequent treatments, concrete that has been cast using rbs Bluelease QD requires only a light brush.

## Directions For Use

- Formwork surfaces to be treated with rbs Bluelease QD should be clean and dry.
- rbs Bluelease QD should be applied as a thin even film using low pressure spray equipment and any excess material should be removed prior to placement of the concrete.
- New and unsealed timbers should be pre-treated with rbs Bluelease QD with a second application prior to use.

## Packaging

rbs Bluelease QD is available in 20 Litre containers.

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

## Storage

rbs Bluelease QD should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months

## Health & Safety

When working with rbs Bluelease QD suitable protective clothing, eye/face protection and gloves should be worn. For further health and safety information, please refer to the relevant Safety Data Sheet.

## Technical Data

Appearance	Clear amber liquid
Specific Gravity @ 15.6°C	0.813
Flash Point (PMCC)	38°C
Viscosity cSt @ 40°C	10.8
Coverage	30-60m <sup>2</sup> per litre
Pour Point	< -5°C

## Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy themselves that each product is fit for the purpose for which they intend to use it. Ensure that the actual conditions of use are suitable, and that in the light of our continual research and development programme, the information relating to each product has not been superseded.

**Resapol**   
**Foundation**

Giving back *with every pack*

For more information on the Resapol Foundation, please visit our website at [www.resapol.com](http://www.resapol.com).

## Resapol Ltd

Unit D4, Moss Industrial Estate, Walter Leigh Way,  
Leigh, Lancashire WN7 3PT

T 0800 083 1942 E [sales@resapol.com](mailto:sales@resapol.com)

[www.resapol.com](http://www.resapol.com)