

rbs Driveseal

Description

rbs Driveseal is a low viscosity, penetrating colourless sealer with sand stabilising properties, it consolidates and binds sand joint particles to prevent sand loss.

It is based on a carefully sourced blend of chemicals. rbs Driveseal will greatly increase concrete surface anti-abrasion properties particularly on concrete carriageways, paving and walkways.

Ideal for imprinted concrete, block paving and standard concrete driveways.

Advantages

- Protects many surfaces from abrasion and water penetration.
- Consolidates floor surfaces.
- Can be used on concrete carriageways, walkways, pavements and car parks.
- Single component, ie no mixing involved.
- Can be used both internally and externally.
- · Gives attractive gloss finish.

Directions For Use

- rbs Driveseal is supplied as a ready to apply product by roller or non-atomising spray.
- Do not over apply and brush out any runs that may occur.
- After about 20 minutes the sealer should have soaked into the concrete, and then further coats should be applied until no more material is absorbed.
- Allow 2 to 3 hours to elapse between coatings.
 Normally 2 coatings are sufficient but on 3 coatings may be needed on very porous surfaces.
- Use only in well ventilated areas and away from sources of ignition.

Technical Data

Appearance	Low viscosity
Specific Gravity @ 15.6°C	0.907
Flash Point (PMCC)	43°C
Viscosity cSt @ 40°C	N/A
Coverage	3-6m² per litre
Recommended Dilution	None required

Packaging

rbs Driveseal is available in 5, 20 and 200 litre containers. IBC's available on request.

Storage

rbs Driveseal should be stored in metal containers under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months, if unopened.

Once opened replace lid immediately after use and use within 2 weeks.

Health & Safety

When working with rbs Driveseal suitable protective clothing, eye/face protection and gloves should be worn. Areas where this product is being applied must be well ventilated.

For further health and safety information, please refer to the relevant Safety Data Sheet.

Page 1 of 2 Revison Date: July 2024



rbs Driveseal

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy themselves that each product is fit for the purpose for which they intend to use it. Ensure that the actual conditions of use are suitable, and that in the light of our continual research and development programme, the information relating to each product has not been superseded.

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use

Resapol Ltd

Unit D4, Moss Industrial Estate , Walter Leigh Way, Leigh, Lancashire WN7 3PT T 0800 083 1942 E sales@resapol.com www.resapol.com



Giving back with every pack

For more information on the Resapol Foundation, please visit our website at www.resapol.com.